



ROHS Compliant

| | | | | | | |
|------|--------|-----------|-------------|------|---------|------|
| REV. | ECN NO | LOCATIONS | DESCRIPTION | DATE | REVISER | APPD |
| | | | | | | |

Note:

Specification:

1. Current rating: 1 A Max.
2. Dielectric withstanding voltage: 500 V(ac) for 1 minute.
3. Contact resistance: 30 mΩ Max.
4. Insulation resistance: 1000 MΩ Min at DC 500V.
5. Temperature range: -55°C~+105°C

| | | | | | |
|-----|-------------|------|-------------------|---------------------|-----------------------------------|
| 7 | Clip | 44 | Stainless steel | T=0.10mm | NO |
| 6 | 8.0 Nut | 2 | Brass | H4.75*8.0 | 80u"min Nickel Plated |
| 5 | 3B Nut | 2 | Brass | H4.75*4.75 | 80u"min Nickel Plated |
| 4 | Back-shell | 1 | Cold Rolled Steel | T=0.40mm | Cu:40u"min. 80u"min Tin Plated |
| 3 | Front-shell | 1 | Cold Rolled Steel | T=0.40mm | Cu:40u"min. 80u"min Nickel Plated |
| 2 | | | | | |
| 1 | Housing | 2 | P.B.T | UL 94-V0 | Black |
| No. | Part Name | Q'ty | Material | Remarks & Thickness | Finish |

| | | | | | |
|-----------------------|-----------|----------------------|--|--------------------------|---------------|
| PART NO: | | MATERIAL: | | | |
| MODEL NO: | | FINISH: | | | |
| UNIT: mm | SIZE: A4 | COLOR: | | PART NAME: | |
| TOLERANCE UNSPECIFIED | | DR: 段林麗 '06/04/05 | | D-SUB HDD CRIMP 44PIN(M) | |
| .x ±0.30 | .xx ±0.20 | CHK: Kevin '06/04/05 | | DWG NO: S/A-122 | REV: A0 |
| .xxx ±0.10 | ANG. ±1° | APP: Kent '06/04/05 | | SCALE: 1:1 | SHEET: 1 of 1 |

