| 2.00111111 1 10111 1111 0111 0 0 1 10 0 0 1 10 0 0 1 | | 2011 | | | |
|--|--|--------------------------|---|-----------|-----|
| | | R | EV ECN NO. | APP. | DA |
| | | | | | |
| | | | | | |
| | 6.70±0.20 | | | | |
| | | SPECI | FICATION | | |
| | 9 | | rent Rating: | | |
| | 4.85±0.20 | | hstanding Voltage: | | |
| | 4, | | VAC (1 min.) ulation Resistance: | | |
| | | 100 | 00 Megohms MIN. | | |
| | A±0.30 | 30 | tact Resistance: Milliohms MAX. | | |
| | | | erating Temperature: O'C to +85°C | | |
| 2.0±0.10 0.50±0.05 | 0.20±0.01 | | ention Force: | | |
| 2.0*(No.of Contacts/2-1)±0.25 | 2.0±0. | 20 450 | Dg MIN. | | |
| 2.0*No. of Contacts/2±0.30 | | MATER | RIAL | | |
| · · · · · · · · · · · · · · · · · · · | | | * Contact: Phosphor Bronze | | |
| | | | ulator: NYLON 66 & 30% G. ting: All Gold | .F. | |
| | | | berofPin | | |
| | | * 80 | | | |
| in Chart | 2.00±0.05 | | | | |
| Pin A | + + + + | | | | |
| 1 3.0 | 4 + + - | FIFPAR | TS Co.,Ltd | | |
| 2 | Ø0.80±0.05 90000000000000000000000000000000000 | 0.0± SCALE: TITLE: | PART NO. | | |
| 3 | Recommended P.C. Board | 0.00± 1.NIT. 2.00X2.00MM | (.079"*.079") er R/A Dual Row | | TS |
| 4 | Hale Layout | | ON 66 + 30% GF CHK BY: | | |
| | | DWG NO FI | IO 7 Camina DR BY: | E DIIGINE | :00 |

DWG. NO. FH07 Series

DR BY:

E - BUSINESS