

# 24/25

Gas Tested	CO In The Air
Measuring Range	0~1000ppm
Resolution	1ppm
Minimum Reading	1ppm
Accuracy	±5% (f.s) or ±10ppm
Response Time	60 Seconds
Sensor Type	Electrochemical CO Sensor
Buzzer Alarm Setup	✓
Set Up and Review the Upper and Lower Alarm Limit	✓
MAX, AVG, Data Hold	✓
Auto Power Off	✓
Low Battery Indication	✓
LCD Backlight	✓
Operating Environment	0~50°C, 32~122°F; 10~90%RH
Storage Environment	-10~80°C, -14~176°F; 10~75%RH
Unit Size	55.7*29.9*135.5mm
Weight	104g
Standard Quantity Per Carton	60PCS
Standard Carton Size	43.9*35.9*30.3cm
Standard Carton Gross Weight	11.8KG
power	2x1.5V AAA Batteries



Carbon Monoxide Meter  
GM8805

Common sources of carbon monoxide potential danger: the lack of maintenance of the stove, gas stove or fireplace. Clogged chimney exhaust pipe. Lack of maintenance of gas, oil or oil refining equipment. Internal combustion engines (such as: automotive, lawn mowers, hair dryer.)



Response Time	2 seconds
Warm Up Time	60seconds approx (25°C, 60%RH environment)
Continuous Operation Time	8hours (varying with operating status)
Low Battery Indication	3±0.2V
Operation Temperature	0~52°C
Adjustable Detection Control	✓
Reset Button on the Probe Hand	✓
Constant Power Indication	✓
LED Alarm Indication	✓
Unit Size	76*49*220MM
Standard Quantity Per Carton	20PCS
Standard Carton Size	53.0*38.1*30.3CM
Standard Carton Gross Weight	14.4KG
Power	3*1.5V LR14 Battery

Combustible Gas  
Detector GM8800A

Easy one-handed design, accurately detects gas leaks with sound and light alarm indication.