



SCHEMATIC

PJ-324M	PJ-324M-1	PJ-324M-2	PJ-324M-3	PJ-324M-4

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: $d0.03\Omega$;
3. Insulation resistance: $e100M\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

8	HOUSING	1	PBT
7	COVER	1	PC
6	AXIS SUPPORT	1	H59 BRASS
5	5#CONTACT FOOT	1	PHOSPHOR BRONZE
4	4#CONTACT FOOT	1	H62 BRASS
3	3#CONTACT FOOT	1	H62 BRASS
2	2#CONTACT FOOT	1	PHOSPHOR BRONZE
1	1#CONTACT FOOT	1	H62 BRASS
NO.	DESCRIPTION	QTY	MATERIAL
			PLATING

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1
	PHONE JACK	PJ-324M	TOLERANCE	ANGLES
			0.15	数1.5
			SCALE	VER
			3:1	1

DESIGNER BY:			旭日佳电子有限公司 BEST SUN ELECTRONIC CO., LTD
CHECK BY:			
APPROVED BY:			