


# 02/03



Compared with the traditional contact type temperature meter, it features quick response, high precision, and contactless without consumable materials, widely applied in fields of labs, chemicals, machinery, environment check, heating and cooling system and non-injure testing.




**Infrared Thermometer GM270**

Temperature Range	-32 ~ 280°C (-26~536°F)
Accuracy	±1.5% or ±1.5°C Whichever is greater
Repeatability	±1% or ±1°C
Distance Spot Ratio	GM270: 8:1
Emissivity	0.95
Resolution	0.1°C/0.1°F
Response Time	500ms
Wavelength	8-14 μm
°C/F Selection	✓
Data Hold Function	✓
Laser Target Pointer ON/OFF Selection	✓
Backlight ON/OFF Selection	✓
Auto Power Off	✓
Standard Quantity Per Carton	60PCS
Unit Size	29.5*53*98mm
Standard Carton Size	42.8*39.5*36CM
Standard Carton Gross Weight	8.3KG
Power	9V 6F22 Battery

Temperature Range	-50 ~ 380°C (-58~716°F)
Accuracy	±1.5% or ±1.5°C Whichever is greater
Repeatability	±1% or ±1°C
Distance Spot Ratio	GM320: 12:1
Emissivity	0.95
Resolution	0.1°C/0.1°F
Response Time	500ms
Wavelength	8-14 μm
°C/F Selection	✓
Data Hold Function	✓
Laser Target Pointer ON/OFF Selection	✓
Backlight ON/OFF Selection	✓
Auto Power Off	✓
Standard Quantity Per Carton	60PCS
Unit Size	37.7*93.1*142.6mm
Standard Carton Size	42.5*41.7*41.4CM
Standard Carton Gross Weight	10.8KG
Power	9V 6F22 Battery



**Infrared Thermometer GM320**



**Infrared Thermometer GM300**

Temperature Range	-50 ~ 420°C (-58~788°F)
Accuracy	±1.5% or ±1.5°C Whichever is greater
Repeatability	±1% or ±1°C
Distance Spot Ratio	12:1
Emissivity	0.95
Resolution	0.1°C/0.1°F
Response Time	500ms
Wavelength	8-14 μm
°C/F Selection	✓
Data Hold Function	✓
Laser Target Pointer ON/OFF Selection	✓
Backlight ON/OFF Selection	✓
Auto Power Off	✓
Unit Size	43*101*153mm
Standard Quantity Per Carton	60PCS
Standard Carton Size	52.0*40.5*45.9CM
Standard Carton Gross Weight	14.6KG
Power	9V 6F22 Battery