


Pos	A	B	C	D	E
9	16.92	24.99	30.81	8.38	12.50
15	25.25	33.32	39.14	8.38	12.50
25	38.96	47.04	53.04	8.38	12.50
37	55.42	63.50	69.32	8.38	12.50
50	52.81	61.11	66.93	11.07	15.37

Specifications:  
 Current Rating:3.0A AC/DC  
 Voltage Rating:250V AC/DC  
 Contact Resistance:30m ohm. max.  
 Insulation Resistance: 5,000M ohm. min.  
 Withstanding voltage:1,000V AC/Minute  
 Operating Temperature Range:-40°C ~ +85°C  
 Material and Finish  
 Insulator:High Temp. Plastic(PBT UL94V-0)  
 Insulator Color:Black  
 Contact:Copper Alloy Nickel Undercoated,  
 Selective Gold Plated  
 Finish:Metal Iron With Tin Plated

How To Order  
 5503-XXP-XX-F1  
 Lead Free  
 Blank:Standard type  
 CS:Rear Rivet  
 CC:Front Rivet  
 P:Male  
 No.Of Positions



RoHS Compliant

F				DRAWN: CEL KING	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	 繼德工業股份有限公司 <b>Neltron Industrial Co., Ltd.</b>	DESCRIPTION: D-SUB Crimp Type Male Housing	SIZE <b>A4</b>
E			CHECKED: JEREMY LIU	UNIT: MM SCALE: 1:1				
D				APPROVAL: MIKE WU	SHEET: 1 / 1	PART NO: 5503-XXP-XX-F1		
C					PROJECTION:			
B								
A	30-Jun-2005	(PC0052)	CEL KING					
REV	DATE	FILE	BY					