

# CERTIFICATE OF CALIBRATION

## SERIAL NO.&CERTIFICATE NO.

<u>PART NO</u>	<u>SET TORQUE</u>	<u>LOWER</u>	<u>UPPER</u>	<u>ACTUAL READING</u>
	Nm	Nm	Nm	Nm
T-60	25	24.0	26.0	_____
	15	14.4	15.6	_____
	5	4.8	5.2	_____
T-80	110	105.60	114.40	_____
	68	65.28	70.72	_____
	19	18.24	19.76	_____
T-150	210	201.60	218.40	_____
	126	120.96	131.04	_____
	42	40.32	43.68	_____
T-250	350	336.0	364.0	_____
	210	201.6	218.4	_____
	70	67.2	72.8	_____
T-300	450	432.0	468.0	_____
	275	264.0	286.0	_____
	65	62.4	67.6	_____
T-500	700	672.0	728.0	_____
	420	403.2	436.8	_____
	140	134.4	145.6	_____
T-700	980	940.8	1019.2	_____
	560	537.6	582.4	_____
	140	134.4	145.6	_____

The limits shown and the test equipment used for this calibration comply with the requirements of:

**BSEN 26789 & ISO 6789 ASME B107.14M & DIN3122.**

The accuracy of the test equipment used is  $\pm 1\%$

TESTED BY: \_\_\_\_\_

DATE: \_\_\_\_\_

PLACE OF PURCHASE:

DATE OF PURCHASE: