


### SCHEMATIC



### SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance:  $d0.03\Omega$ ;
3. Insulation resistance:  $e100M\Omega$  (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. life test: 5,000 cycles.

6	NUT	1	BRASS	Ni-Plating
5	HOUSING	1	ABS/PBT	
4	AXIS SUPPORT	1	H62 BRASS	Ni-Plating
3	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
2	CURVE PIECE	1	H62 BRASS	Sn-Plating
1	FLAT PIECE	1	H62 BRASS	Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

UNIT: MM 	TYPE: PHONE JACK	MODEL NO: PJ-301M	PAPER NO: A4		PAGE 1 OF 1	
			TOLERANCE	ANGLES	SCALE	VER
			0.15	数1.5	3:1	1

DESIGNER BY:	
CHECK BY:	
APPROVED BY:	



**旭日佳电子有限公司** □  
 BEST SUN ELECTRONIC CO., LTD