

HIGH TEMPERATURE EPOXY

832HT-PART A

Safety Data Sheet

Section 1: Product and Company Identification

Product Identifier and Other Means of Identification

Product Name: High Temperature Epoxy: Encapsulating and Potting Compound**SDS Code:** 832HT-Part A**Related Part #:** 832HT-375ML, 832HT-3L, 832HT-60L

Recommended Use and Restriction on Use

Use: Epoxy resin for use with hardeners to pot devices or encapsulate components**Uses Advised Against:** Not for use as a spray coating

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

☎ 1-800-340-0772

FAX 1-800-340-0773

E-MAIL: support@mgchemicals.comWEB www.mgchemicals.com

☎ 1-905-331-1396

FAX 1-905-331-2682

E-MAIL: info@mgchemicals.comE-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents
USA or CANADA: Call CHEMTREC ☎: **1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7CANADA: Call CANUTEC ☎: **1-613-996-6666** or ***666** on cellular phones

HIGH TEMPERATURE EPOXY

832HT-PART A

Section 2: Hazards Identification

Classification of Hazardous Chemical




WHMIS Classification



D2A – Very Toxic (Carcinogenicity IARC: 2B); D2B – Toxic Material (Skin/Eye Irritation; Skin Sensitization in Humans)

Note: The possible carcinogenicity warning applies to inhalable dust. Aerosolization and misting should be avoided and are not expected to occur for normal uses.

GHS Categories


Criteria		Category	Signal Word	Pictograms
Sensitization	Skin sensitizer	1	Warning	
Skin Irritation		2A	Warning	
Eye Irritation		2	Warning	
Carcinogenicity		2	Warning	
Environmental Hazard	Chronic Aqua. Tox.	2	Warning	
Environmental Hazard	Acute Aqua. Tox.	2	—	

Other Classifications

HMIS® RATING

HEALTH:	2
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:




0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Continued on the next page

HIGH TEMPERATURE EPOXY

832HT-PART A

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H319: Causes serious eye irritation H317: May cause allergic skin reaction H312: Harmful in contact with skin
	H351: Suspected of causing cancer
	H411: Toxic to aquatic life with long lasting effects
	Precautionary Statements
	P102: Keep out of reach of children. P260: Do not breathe fume/gas/vapors/spray. P280: Wear protective gloves/eye protection. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P302 + P352 + P361 + P353: IF ON SKIN: Wash with plenty of water. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. P310: Immediately call a POISON CENTER or doctor

Other Hazards

Not applicable

Section 3: Hazardous Ingredients

CAS #	Chemical Name	Wt%
28064-14-4	phenyl glycidyl ether/ formaldehyde copolymer	85-99%
1333-86-4	carbon black	0.1-0.5%

HIGH TEMPERATURE EPOXY

832HT-PART A

Section 4: First Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305
Symptoms	Immediate: <i>irritation, redness, pain</i>
Response	P351: Rinse cautiously with water for several minutes. P338: Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists	P313: Get medical attention.
IF ON SKIN	P302
Symptoms	Immediate: <i>irritation, redness;</i> Delayed: <i>rash</i>
Response	P352: Wash with plenty of water. P362+ P364 + P272: Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.
If skin irritation, rash occurs, or concerned	P313: Get medical advice/attention.
IF INHALED	P304 (<i>Not a likely route of exposure under normal use</i>)
Symptoms	Immediate: <i>cough, respiratory system irritation</i>
Response	P340: Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.
If feeling unwell	P312: Call a POISON CENTRE/doctor.
IF SWALLOWED	P301 (<i>Not a likely route of exposure under normal use</i>)
Symptoms	Immediate: <i>irritation</i>
Response	P330: Rinse mouth. P331: Do NOT induce vomiting.
If feeling unwell	P312: Call a POISON CENTRE/doctor.

HIGH TEMPERATURE EPOXY

832HT-PART A

Section 5: Fire Fighting Measures

Auto-ignition Temperature	Not Established	Flash Point ^{a)}	>122 °C [>252 °F]	LFL [LEL] ^{b)}	Not Established
				UFL [UEL]	Established

In case of fire P370

Response P378: Use dry chemical, carbon dioxide, or chemical foam to extinguish. Use water spray to cool containers.

Combustion Products Produces CO, CO₂, and phenolic molecules.

Fire-Fighter Wear self-contained breathing apparatus for fire fighting

General Information Prevent fire-fighting wash from entering waterway or sewer system.

a) Supplier value for the component with the lowest know flash point

b) LFL = Lower Flammability [or Explosion] Limit (in volume %);

UFL = Upper Flammability [or Explosion] Limit (in volume %)

Section 6: Accidental Release Measures

Personal Protection: See Section 8. Avoid breathing the mist/vapors.

Containment Remove all sources of ignition.

Cleaning Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe up further residue with paper towel wetted with alcohol (or other suitable organic solvent) and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.

RECOMMENDATION: Use a plastic, stainless steel, or carbon steel container.

Disposal Dispose of spill waste according to Section 13.

HIGH TEMPERATURE EPOXY

832HT-PART A

Section 7: Handling and Storage

Prevention P262: Do not get in eye, on skin, or on clothing.

P261 + P271 + P284: Avoid breathing fume/vapors. Use only outdoors or in well ventilated area. In cases of inadequate ventilation wear respiratory protection.

P270: Do not eat, drink, or smoke when using this product.

RECOMMENDATION: Protect from high heat. Do NOT process in a fashion that causes mist or fumes.

Handling P280: Wear protective gloves/clothing/eye protection.

RECOMMENDATION: Wear neoprene, butyl rubber, nitrile or other impervious gloves with breakthrough time greater than intended use period.

P264: Wash hands thoroughly after handling.

Storage P403 + P233+ P235: Keep Container tightly closed. Store in a well-ventilated area. Keep cool.

RECOMMENDATION: Keep in a dry and clean area, away from incompatible substances.

Section 8: Exposure Controls/Personal Protection

Routes of Entry

Eyes, ingestion, inhalation, and skin

Substances with Occupational Exposure Limit Values

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
Carbon black ^{a)}	ACGIH	3.5 mg/m ³	—
	U.S.A. OSHA PEL	3.5 mg/m ³	—
	Canada AB	3.5 mg/m ³	—
	Canada BC	3 mg/m ³	—
	Canada ON	3.5 mg/m ³	—
	Canada QC	3.5 mg/m ³	—

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH², OSHA, and Canadian provinces exposure limits were consulted. Limits from by RTECS database¹ of the Canadian Centre for Occupational Health and Safety (CCOHS) a data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

Continued on the next page

HIGH TEMPERATURE EPOXY**832HT-PART A****Engineering Controls****Ventilation**

Keep airborne concentrations below exposure limits. Because carbon black is bound to the liquid mixture; the airborne hazard is present only if the conditions of use result in aerosolization or misting.

RECOMMENDATION: If the product is heated at high temperatures or worker is allergic, consider using a full mask with organic vapor cartridges.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

Wear appropriate protective clothing to prevent skin contact.

RECOMMENDATION: Use of protective gloves in butyl rubber, latex, neoprene, or other chemically resistant gloves.

Respiratory Protection

If exposed to mist, wear respirator such as a half-mask respirator.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has filter cartridges appropriate for the ingredients listed in section 3 of this MSDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

HIGH TEMPERATURE EPOXY

832HT-PART A

Section 9: Physical and Chemical Properties

Physical State	Liquid	Appearance	Black
Odor	Mild aromatic	Odor Threshold	Not established
pH	Not available	Specific Gravity	0.963
Solubility in Water	Insoluble	Freezing/Melting Point	Not available
Flash Point ^{a)}	>122 °C [>252 °F]	Vapor Pressure @ 20 °C	Not available
Boiling Point	>150 °C [>302 °F]	Evaporation Rate	Not available
Lower Flammability Limit	Not available	Upper Flammability Limit	Not available
Auto-ignition Temperature	Not available	Decomposition Temperature	Not available
Viscosity @25 °C	54 800 cSt	Vapor Density	Not available
Partition Coefficient	Not established		

a) The closed cup flash point for component with the lowest reported value.

Section 10: Stability and Reactivity

Stabilities	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Excessive heat, and incompatible substances. Do not use in a way that forms a mist or aerosolize the product
Incompatibilities	Strong oxidizing agents, strong bases, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

HIGH TEMPERATURE EPOXY**832HT-PART A****Section 11: Toxicological Information****Routes of Exposure**

Eyes, ingestion, inhalation, and skin

Symptoms Summary

- Eyes** Causes serious eye irritation. May also cause eye redness or pain.
- Skin** May cause mild to moderate skin irritation and allergic skin reactions.
- Inhalation** *Not a likely route of exposure due to low volatility.* Inhalation of vapors or mist may cause irritation to the nose, throat and lung (upper respiratory tract).
- Ingestion** *Not a likely route of exposure.* No acute toxicity effect known. See skin and inhalation symptoms.
- Chronic** Prolonged or repeated exposure to the uncured epoxy resins used may cause dermatitis and sensitization.
- Long term exposure to carbon black dust or mist may cause cancer.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation	TCLo inhalation
phenyl glycidyl ether/ formaldehyde copolymer	4 000 mg/kg Rabbit ^{a)}	Not available	6 000 mg/kg Rabbit ^{a)}	Not available
carbon black	>15 g/kg Rat	>3 g/kg Rabbit	Not available	1.6 mg/m ³ 7 h Rat

Note: Representative toxicity data from by RTECS database of the Canadian Centre for Occupational Health and Safety (CCOHS)¹ data from supplier MSDS were also consulted.

a) Supplier MSDS

- Skin corrosion/irritation** Skin irritant
- Serious eye damage/irritation** Causes serious eye irritation.
- Sensitization (allergic reactions)** The epoxy resin components (CAS# 28064-14-4) may cause skin sensitization in humans

Continued on the next page

HIGH TEMPERATURE EPOXY**832HT-PART A****Carcinogenicity**

(risk of cancer)

The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures. Because the carbon black is bound in the epoxy liquid mixture, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen

NTP: Not listed

Mutagenicity

(risk of heritable genetic effects)

No data available

Reproductive Toxicity

(risk to sex functions)

No data available

Teratogenicity (risk of

fetus malformation)

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

Viscosity at 40 °C is $\gg 20.5 \text{ mm}^2/\text{s}$, thus not classified as aspiration hazard.

HIGH TEMPERATURE EPOXY**832HT-PART A****Section 12: Ecological Information**

The ecotoxicity of the mixture was estimated by the calculation method using the summation of classified ingredients. The IMDG Code criteria and the raw-material MSDS along with supporting data for the classification of registered substances from the European Chemical Agency database (<http://echa.europa.eu>) were used.

In Europe, similar epoxy resins with CAS# 28064-14-4 are generally classified as category 2 marine pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L. Chronic toxic effects have been suggested.

Acute Ecotoxicity

Category 2

GHS Code: Hazard Statement

H401: Toxic to aquatic life

P273: Avoid release to the environment

P391: Collect spillage

Chronic Ecotoxicity

Category 3

GHS Code: Hazard Statement

H411: Toxic to aquatic life with long lasting effects

P273: Avoid release to the environment

P391: Collect spillage

Biodegradability

The content is not readily biodegradable.

Section 13: Disposal Information

P501: Dispose of contents in accordance with all local, regional, national, and international regulations.

Continued on the next page

HIGH TEMPERATURE EPOXY**832HT-PART A****Section 14: Transport Information****Ground**

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA CFR 49 Regulations** (Parts 100 to 185). **ADR** (European Agreement Concerning the International Carriage of Dangerous Goods by Road, and **ADN** (Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways).

Sizes 5 liter and under

Limited Quantity

Note: The 832HT-375ML, 832HT-3L and 832HT-12L are composed of separate containers which meet this inner packaging limit.



All sizes greater than 5 liter

UN number: UN3082

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, N.O.S. (Reaction product: bisphenol-F-(epichlorhydrin))

Class: 9

Packing Group: III

Marine Pollutant: Yes

**Air**

Refer to ICAO-IATA Dangerous Goods Regulations.

All sizes

UN number: UN3082


Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, N.O.S. (Reaction product: bisphenol-f-(epichlorhydrin))

Class: 9

Packing Group: III

Marine Pollutant: Yes

Pkg Inst: 964. ERG Code: 9L



Continued on the next page

HIGH TEMPERATURE EPOXY**832HT-PART A****Sea**

Refer to IMDG regulations.

Sizes 5 liter and under

Limited Quantity

Note: The 832HT-375ML, 832HT-3L and 832HT-12L are composed of separate containers which meet this inner packaging limit.



All sizes greater than 5 liter

UN number: UN3082

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, N.O.S. (Reaction product: bisphenol-F-(epichlorhydrin))


Class: 9

Packing Group: III

Marine Pollutant: Yes

EmS#: F-A, S-F

Stowage and Segregation: Category A



Note: Component supplier SDS transportation sections and labeling were consulted. All involved staff of shipper must be appropriately trained before involvement with the transport of this product, or work under direct supervision of a trained person.

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

HIGH TEMPERATURE EPOXY**832HT-PART A****USA****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substance subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product does not contain any of the listed substances.

Europe**RoHS**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

MSDS Prepared by Michel Hachey
Date of Issue 03 July 2013
Supersedes 20 January 2011
Reason for Changes: Change to GHS format

Reference

1) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

2) ACGIH 2011 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2011).

Continued on the next page

HIGH TEMPERATURE EPOXY**832HT-PART A****Abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists

GHS: Globally Harmonized System of Classification of Labeling of Chemicals

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50%

N/A Not Applicable

N/E Not Estimated

PEL Permissible Exposure Limit

STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average

VOC Volatile Organic Content

WEEL Workplace Environmental Exposure Levels

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.