



UT350 SERIES

Sound Level Meters

UT351/UT352



UT351



UT352

SPECIFICATIONS

Measurement Functions	Models	
	UT351	UT352
Total Range	30 to 130dB	30 to 130dB
Maximum Level	130dB	130dB
Accuracy	±1.5dB	±1.5dB
Range Selections	30 to 80dB, 50 to 100dB, 60 to 110dB, 80 to 130dB	
Frequency Range	31.5Hz to 8000Hz	31.5Hz to 8000Hz
Frequency Weighting	A and C	A and C
Time Weighting	FAST (125ms)	FAST (125ms)
	SLOW (1 second)	SLOW (1 second)
Analogue Bar Graph	30~130dB	30~130dB
Warning	Over-Range "OVER", Under-Range "UNDER"	
Analogue Outputs	AC: 0.707Vrms full scale; Output impedance: around 600Ω	
	DC: 2Vrms full scale; 10mV/dB; Output impedance around 100Ω	
Max/Min Mode	✓	✓
Data Hold	✓	✓
Display Backlight	✓	✓
Sleep Mode	✓	✓
Low Battery Display	4.8V	4.8V
Data Logging		63 data sets

GENERAL CHARACTERISTICS

Power	1.5V Battery (AA) × 4
LCD Size	53 × 41 mm
Product Colour	Red and Grey
Product Net Weight	330g
Product Size	273 × 70 × 39mm
Standard Accessories	Batteries, English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	670 × 385 × 300 mm (0.077CBM Per Standard Carton)
Standard Carton Gross Weight	18kg