



Sample photo

Order symbol: PC M 95 G
Product nbr: 8724318
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074002310
EI. number:
 Finland 3423419
 Denmark 8212001763
 Italy 7201060
 Sweden 2536829

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:		L	W	H	Rating:
mm:		230	140	95	Ingress Protection (EN 60529): IP 66/67
inch:		9.1	5.5	3.7	Impact Resistance (EN 50102): IK 08
Materials:					
Material:		PC			
Base colour:		RAL 7035			
Cover colour:		RAL 7035			
Cover screws material:		Polyamide			
Cover screws colour:		Grey			
Gasket material:		Polyurethane			
Temperatures:					
Short term:		-40 ... 120 °C			
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
M-MP		Mounting plate			
CHM-3		DIN-35 Mounting rail			
FM-3		DIN-35 Mounting rail			
FP 22046		Mounting foot kit (4 pcs)			
					Certificates:
					Germanischer Lloyd (GL)
					Underwriters Laboratories
					Canadian Standards Association
					Fimko
					Europe EN 50298 1998
					UL Canada
					Gost R
					Electrical insulation: Totally insulated
					Halogen free (DIN/VDE 0472, Part 815): Yes
					UV resistance: UL 508
					Flammability Rating (UL 746 C 5): UL 94 5V
					Glow Wire Test (IEC 695-2-1) °C: 960
					NEMA Class: NEMA 1, 4X, 6, 6P, 12, 13

